



Mini circuit breaker, QO, 15A, 1 pole, 120/240VAC, 10kA, bolt on

QOB115

Main

Product	Miniature circuit-breaker	
Range	QO	
Current Rating	15 A	
Voltage Rating	120/240 V AC 120 V AC	
Mounting Type	Bolt-on	
Number of Poles	1P	
Circuit Breaker Type	Standard	
Ratings	HACR and Switching Duty rated	
Electrical Connection	Pressure plate	

Complementary

Interrupt Rating	10 kA 120/240 V AC 10 kA 120 V AC
Number of Panel Spaces	1
Wire Size	AWG 14AWG 8 copper or aluminum
Tightening Torque	35.4 lbf.in (4 N.m)
Height	3.0 in (76 mm)
Width	0.7 in (19 mm)
Depth	2.9 in (74 mm)
Net weight	0.280 lb(US) (0.127 kg)

Environment

Certifications	UL listed CSA
Ambient Rating	104 °F (40 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.30 in (8.382 cm)
Package 1 Width	0.80 in (2.032 cm)
Package 1 Length	3.40 in (8.636 cm)

Package 1 Weight	4.5 oz (127.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.30 in (8.382 cm)
Package 2 Width	0.80 in (2.032 cm)
Package 2 Length	7.80 in (19.812 cm)
Package 2 Weight	2.851 lb(US) (1.293 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	8.00 in (20.32 cm)
Package 3 Width	7.90 in (20.066 cm)
Package 3 Length	17.10 in (43.434 cm)
Package 3 Weight	29.050 lb(US) (13.177 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	18
Environmental Disclosure	Product Environmental Profile

Use Better


Materials and Substances		
Packaging made with recycled cardboard	No	
Packaging without single use plastic	Yes	
EU RoHS Directive	Compliant	
SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99	
REACh Regulation	REACh Declaration	
Halogen content performance	Halogen free product	

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration

Dimensions



Dimensions are approximate. Refer to technical documentation for additional detail

Product data sheet

QOB115

Image of product / Alternate images

Alternative

Technical Benefits Thermal Magnetic Breaker



Miniature circuit breaker rated at 15A



Product characteristics conformity is certified by the Underwriters Laboratories (UL)



Bolt-On Type with Visi-Trip Indicator to quickly identify trips



Protects against overloads and short-circuits



The current capacity that this circuit breaker is able to interrupt before breaking is 10kA



Compatible with QO electrical panels and CSEDs with 1 spaces





