

Selector swich, metal Spring return from right Short lever position, B  
Cam 3 position Operator only white insert Non-Illuminated UL file  
E22655 in Vol. 6 (7) Sec. 13 (2)

Design of the product	Actuator round
-----------------------	----------------

### Enclosure

Number of command points	1
Delivery state	No
<ul style="list-style-type: none"> <li>as a kit</li> </ul>	No

### Actuator

Design of the operating mechanism	selector switch
Material of the actuating element	plastic
Type of unlocking device	rotate-to-unlatch mechanism
Number of switching positions	3

### Front ring

Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	chrome

### Holder

Material of the holder	Metal
------------------------	-------

### General technical data

Product component	
<ul style="list-style-type: none"> <li>Light source</li> </ul>	No
Degree of pollution	1
Protection class IP	IP66
Operating frequency maximum	600 1/h

### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-35 ... +70 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +85 °C

### Installation/ mounting/ dimensions

Shape of the installation opening	round
-----------------------------------	-------

### Certificates/ approvals

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2BCB>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2BCB>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2BCB>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SA2BCB&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2BCB&lang=en)

last modified:

03/30/2020