## **SIEMENS**

## Data sheet

## US2:52PP2W2AP

30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Point-of-Purchase Kit Push-Pull Operator Non-Illuminated Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic Cap, Red 2 Position Maintained, Pull-to-Release with 1 N.O. - 1 N.C. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards 1 52NL04R (STOP) and 1 52NL04 (STOP) Legend Plate 1 Yellow Backing Plate with Text: EMERGENCY STOP



Figure similar

Enclosure	
Number of command points	1
Delivery state	
● as a kit	No
Actuator	
Material of the actuating element	plastic
Number of contact modules	1
Type of unlocking device	pull-to-unlatch mechanism
Number of switching positions	2
Front ring	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
General technical data	
Product function	
<ul> <li>positive opening</li> </ul>	Yes

Product component			
Light source	No		
Insulation voltage			
<ul> <li>rated value</li> </ul>	600 V		
Surge voltage resistance rated value	4 kV		
Protection class IP	IP66		
• of the terminal	IP20		
Thermal current	10 A		
Auxiliary circuit			
Number of NC contacts for auxiliary contacts	1		
Number of NO contacts for auxiliary contacts	1		
Operating current at AC-15			
• at 110 V rated value	60 A		
• at 230 V rated value	30 A		
• at 400 V rated value	15 A		
• at 500 V rated value	12 A		
Connections/ Terminals			
Type of electrical connection	screw-type terminals		
Tightening torque of the screws in the bracket	20 N·m		
Tightening torque [lbf·in]			
<ul> <li>with screw-type terminals</li> </ul>	8 lbf·in		
Ambient conditions			
Ambient temperature			
<ul> <li>during operation</li> </ul>	-35 +70 °C		
<ul> <li>during storage</li> </ul>	-40 +85 °C		
Installation/ mounting/ dimensions			
Shape of the installation opening	round		
Certificates/ approvals			
Further information			
Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP2W2AP Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP2W2AP Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP2W2AP			
		Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP2W2AP⟨=en	
		laat madified	03/08/2020

last modified:

03/08/2020