

General Service

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life (hrs)	Filament type	Finish/ Color	Case qty (inner/master)
A15									
MOL : 3 1/2 in. (89 mm) LCL : 2 3/8 in. (60 mm)									
50125	15A15/CL/5M/130V/STD	15	E26	130	85	5 000	C-9	Clear	6/60
50166	15A15/F/5M/130V/STD	15	E26	130	80	5 000	C-9	Frost	6/60
50145	25A15/CL/5M/130V/STD	25	E26	130	135	5 000	C-9	Clear	6/60
50126	25A15/F/5M/130V/STD	25	E26	130	135	5 000	C-9	Frost	6/60
A19									
MOL : 4 1/4 in. (108 mm) LCL : 3 1/8 in. (79 mm)									
50941	15A19/CL/6M/130V/STD	15	E26	130	80	6 000	C-9	Clear	6/120
50931	25A19/CL/1M/120V/STD/4P	25	E26	120	150	1 000	C-9	Clear	6/120
50932	25A19/F/1M/120V/STD/4P	25	E26	120	140	1 000	C-9	Frost	6/120
50942	25A19/CL/6M/130V/STD/4P	25	E26	130	105	6 000	C-9	Clear	6/120
50943	25A19/F/6M/130V/STD/4P	25	E26	130	100	6 000	C-9	Frost	6/120
B8									
MOL : 3 5/32 in. (80 mm) LCL : 1 7/8 in. (48 mm)									
50638	15B8/F/2.5M/E12/130V/STD	15	E12	130	70	2 500	C-7A	Frost	6/120
50639	25B8/F/2.5M/E12/130V/STD	25	E12	130	115	2 500	C-7A	Frost	6/120
B10									
MOL : 3 29/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)									
50611	15B10/CL/3M/E12/130V/STD	15	E12	130	75	3 000	C-7A	Clear	6/120
50543	25B10/CL/3M/E12/130V/STD	25	E12	130	165	3 000	CC-2V	Clear	6/120
50612	25B10/F/3M/E12/130V/STD	25	E12	130	165	3 000	CC-2V	Frost	6/120
MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)									
50621	25B10/CL/3M/130V/STD	25	E26	130	165	3 000	CC-2V	Clear	6/120
MOL : 3 31/32 in. (101 mm) LCL : 1 25/32 in. (45 mm)									
50548	25B10/CL/3M/E14/130V/STD	25	E14	130	165	3 000	CC-2V	Clear	6/120
50551	25B10/F/3M/E14/130V/STD	25	E14	130	195	3 000	CC-2V	Frost	6/120
B10 Suitable for base up									
MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)									
50624	25B10/F/3M/130V/STD	25	E26	130	165	3 000	CC-2V	Frost	6/120
50622	40B10/CL/3M/130V/STD	40	E26	130	280	3 000	CC-2V	Clear	6/120
50625	40B10/F/3M/130V/STD	40	E26	130	280	3 000	CC-2V	Frost	6/120
MOL : 3 29/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)									
50544	40B10/CL/3M/E12/130V/STD	40	E12	130	280	3 000	CC-2V	Clear	6/120
50613	40B10/F/3M/E12/130V/STD	40	E12	130	280	3 000	CC-2V	Frost	6/120
50545	60B10/CL/3M/E12/130V/STD	60	E12	130	430	3 000	C-7A/3	Clear	6/120
50614	60B10/F/3M/E12/130V/STD	60	E12	130	430	3 000	C-7A/3	Frost	6/120
MOL : 3 31/32 in. (101 mm) LCL : 1 25/32 in. (45 mm)									
50549	40B10/CL/3M/E14/130V/STD	40	E14	130	280	3 000	CC-2V	Clear	6/120
50552	40B10/F/3M/E14/130V/STD	40	E14	130	280	3 000	CC-2V	Frost	6/120
50550	60B10/CL/3M/E14/130V/STD	60	E14	130	430	3 000	C-7A/3	Clear	6/120
50553	60B10/F/3M/E14/130V/STD	60	E14	130	430	3 000	C-7A/3	Frost	6/120
BR30									
MOL : 5 1/8 in. (130 mm) LCL : 3 11/32 in. (85 mm)									
50219	50BR30/FL/5M/130V/STD	50	E26	130	240	5 000	C-9	Frost	6/60
50077	65BR30/FL/5M/ES/130V/STD	65	E26	130	470	5 000	CC-6	Frost	6/60
50079	65BR30/SP/5M/ES/130V/STD	65	E26	130	470	5 000	CC-6	Clear	6/60
BR40									
MOL : 6 9/16 in. (167 mm) LCL : 4 1/4 in. (108 mm)									
50080 ¹	65BR40/FL/5M/ES/130V/STD	65	E26	130	470	5 000	CC-6	Clear	1/12
C7									
MOL : 2 1/8 in. (54 mm) LCL : 1 1/2 in. (38 mm)									
50967	4C7/CL/3M/E12/125V/STD	4	E12	125	25	3 000	C-7A	Clear	1/500
22008	7C7/CL/2M/E12/120V/2P/STD	7	E12	120	26	2 000	C-7A	Clear	30/120

¹ This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.