



Order code	Description	Watts (W)	Base	Volts (V)	Finish	Filament	Average life (hrs)	Initial lumens (lm)	LCL (in.) (mm)	Case qty
BR30										
MOL : 5 1/8 in. (130 mm) Dia. : 3 3/8 in. (95 mm)										
52452	65BR30/FL/5M/ES/130V/ELUME 2P	65	E26	130	Frost	CC-6	5000	590	4 101	60
G16.5										
MOL : 2 3/8 in. (73 mm) Dia. : 2 1/16 in. (52.5 mm)										
52453	25G16.5/CL/3M/E12/130V/ELUME 2P	25	E12	130	Clear	C-7A	3000	160	1 7/8 48	60
52454	40G16.5/CL/3M/E12/130V/ELUME 2P	40	E12	130	Clear	C-7A	3000	315	1 7/8 48	120
G25										
MOL : 4 1/2 in. (115 mm) Dia. : 3 1/2 in. (79 mm)										
52455	40G25/CL/3M/130V/ELUME 2P	40	E26	130	Clear	C-9	3000	350	2 7/8 73	60
52457	40G25/WH/3M/130V/ELUME 2P	40	E26	130	White	C-9	3000	330	2 7/8 73	60
R16										
MOL : 3 1/2 in. (88 mm) Dia. : 2 in. (51 mm)										
52459	40R16/SW/1M/120V/ELUME 2P	40	E26	120	Soft White	CC-6	1000	445	3 1/32 77	60
52460	60R16/SW/1M/130V/ELUME 2P	60	E26	130	Soft White	CC-6	1000	730	3 1/32 77	60
R20										
MOL : 3 1/16 in. (100 mm) Dia. : 2 1/2 in. (63.5 mm)										
52462	30R20/FL/5M/130V/ELUME 2P	30	E26	130	Frost	C-9	5000	135	2 9/16 65	60
61707	45R20/FL/5M/130V/ELUME 2P	45	E26	130	Frost	CC-6	5000	242	2 9/16 65	45
¹ 52463	75R20/FL/5M/130V/ELUME 2P	75	E26	130	Frost	C-9/5	5000	540	2 9/16 65	60

¹This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted

Incandescent Lamps