

Wireless Passive Infrared Detector **WS4904**

Features That Make a Difference:

- Reliable 433 MHz technology
- WS4904P model version provides pet immunity up to 60 lbs (27 kg)
- Digital signal analysis for consistent detection throughout the coverage pattern
- Exceptional catch performance at elevated temperatures
- Patented Multi-Level Signal Processing (MLSP) for accurate detection of human IR energy over a broad range of temperatures
- High-traffic shutdown
- Temperature compensation
- 1 long-life lithium battery included; capable of up to 9 years of battery life
- Sensitivity adjustment to configure the detector for "normal" (high sensitivity) or "hostile" (low sensitivity) environments



Among the most technologically advanced detectors available, the WS4904 achieves superior detection and false alarm prevention through digital signal analysis. Digital information is more accurately analyzed using software and is not subject to signal degradation caused by amplification, noise, distortion or signal clipping. The detector's technology adapts to changing environmental conditions by adjusting critical detection parameters to provide improved consistency of detection over all temperature ranges. Pet owners looking to be protected from false alarms can choose the WS4904P model version, a detector that is immune from pets weighing up to 60 lbs (27 kg).

Accurate Detection


Patented Multi-Level Signal
Processing (MLSP) provides for
more accurate detection of human
IR energy over a broad range of
temperatures. It's able to maximize
catch performance while providing
protection against false alarm
sources such as radio interference,
air vents and insects.


Wireless Reliability

Built with reliable 433 MHz technology, the detector features the latest low-power RF technology to effectively extend battery life. The PCB antenna design provides for more consistent performance and better coverage and sensitivity.



Coverage Pattern





Compatibility

The WS4904 is compatible with the following receivers:

- IMPASSA Self-Contained 2-Way Wireless Security System
- ALEXOR 2-Way Wireless Security System
- SCW9045/9047 Self-Contained Wireless Security System
- PowerSeries Wireless Receivers PC5132-433 / RF5132-433 / RF5108-433 / TR5164-433
- PowerSeries RFK Keypads RFK55XX-433
- MAXSYS Wireless Receivers PC4164-433 / RF4164-433
- WS4920 Wireless Repeater

Specifications

Dimensions	4 ^{1/4} ″ x 2 ^{1/2} ″ x 2 ^{2/16} ″
	(108 mm x 63.5 mm x 54 mm)
Battery	CR123A (3V Lithium)
Battery Life	9 Years (Typical)
Coverage	40 ft x 40 ft (12 m x 12 m)
	Fast Setting
Operating Temperature	10° to 55°C (14° to 131°F)
Relative Humidity	5% to 93%